

VRD37

ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

LARGE DISPLAY
CAPACITY WITH MAXIMUM
ENERGY EFFICIENCY.



> KEY FEATURES

• BMAD Refrigeration System

Ensures rapid and effective cabinet cool down and maintains consistent temperature range with minimum energy consumption

• Electronic Temperature Controller

Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.

• High Efficiency Glass Door

Equipped with double panel glass and low-e film to reduce condensation. Door hinge is equipped with a self-closing system to ensure the door closes safely, and returns to original position, without any damages.

• LED Lighting System

Our LED system uses a fraction of the energy of regular fluorescent lights and requires no replacement for up seven years.

• CFC and HFC Free Cyclopentane Foam

Eco-friendly, recyclable and high efficiency cabinet insulation.

• Electronic Fan Motors


Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer lifespan fan motor.



VRD37

ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

PRODUCT VIEWS



TOP VIEW





FRONT VIEW

SIDE VIEW

Warranty:

Three year limited warranty on all parts and labor, an additional two year warranty on compressor. (USA and Canada only)

Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.

Customer Service: 866-363-0079 | WWW.IMBERAFOODSERVICE.COM

() TECHNICAL SPECIFICATIONS

Capacity 20oz.	Flat: Gravit	490 v: 420
Shelves	10	
Weight Weight w/packaging		434.3 Lbs 197.0 kg 453.0 Lbs 205.5 kg
Shelf Size	W: D:	20 1/2" 520 mm 20 5/8" 524 mm
Dimensions w/packaging	W: D: H:	49 1/2" 1258 mm 32" 813 mm 82 1/2" 2097 mm
Interior Dimensions	W: D: H:	43 1/8" 1095 mm 25 3/4" 652 mm 60 1/2" 1537 mm
Exterior Dimensions	W: D: H:	47 3/8" 1203 mm 30 3/8" 770 mm 78 5/8" 1997 mm

() REFRIGERATION DATA

Energy Consumption	5.170 kWh/day
Voltage	115/60
Horse Power	1/2
AMPS	10.0

() LOGISTIC

Trailer Loads	40': 24 53': 31
Certifications	UL: ✓ ES: ✓
	UL/EPH: ✓

^{*} Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (Low maintenance high performance). Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.