

G319_{STAINLESS}

ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

ITS INNOVATIVE DESIGN AND LARGE CAPACITY MAKE IT IDEAL FOR KITCHENS.



() KEY FEATURES

• BMAD Refrigeration System

Ensures rapid and effective cabinet cool down and maintains consistent temperature range with minimum energy consumption

• Electronic Temperature Controller

Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.

• High Efficiency Glass Door

Equipped with double panel glass and low-e film to reduce condensation. Door hinge is equipped with a self-closing system to ensure the door closes safely, and returns to original position, without any damages.

• LED Lighting System

Our LED system uses a fraction of the energy of regular fluorescent lights and requires no replacement for up seven years.

• CFC and HFC Free Cyclopentane Foam

Eco-friendly, recyclable and high efficiency cabinet insulation.

• Electronic Fan Motors

Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer lifespan fan motor.

Low Maintenance Condenser


Imbera's finless condenser designed to minimize maintenance. Drastically reduces Total Cost of Ownership. Prevents dust that blocks air flow, to save energy and extend the life of the compressor.




G319_{STAINLESS}


ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

PRODUCT VIEWS



TOP VIEW





Warranty:

Three year limited warranty on all parts and labor, an additional two year warranty on compressor. (USA and Canada only)

Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.

Customer Service: 866-363-0079 | WWW.IMBERAFOODSERVICE.COM

() TECHNICAL SPECIFICATIONS

Capacity 20oz.	Flat: Gravity	240 y: 240
Shelves	5	
Weight Weight w/packaging		223.8 Lbs 101.5 kg 240.4 Lbs 109.1 kg
Shelf Size	W: D:	24 3/4" 630 mm 19 5/8" 497 mm
Dimensions w/packaging	W: D: H:	32 1/4" 820 mm 29 7/8" 760 mm 82 5/8" 2100 mm
Interior Dimensions	W: D: H:	25 1/2" 649 mm 21 3/8" 542 mm 60 1/2" 1536 mm
Exterior Dimensions	W: D: H:	29 1/2" 750 mm 27 1/2" 700 mm 78 3/4" 2000 mm

O REFRIGERATION DATA

Energy Consumption	3.040 kWh/day
Voltage	115/60
Horse Power	1/4+
AMPS	5.2

() LOGISTIC

Trailer Loads	40': 42 53': 60
Certifications	UL: ✓ ES: ✓
	UL/EPH: ✓

^{*} Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (Low maintenance high performance). Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.