



ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

WITH ITS LARGE CAPACITY, THIS FREEZER PRESERVES YOUR FROZEN PRODUCT WHILE PROVIDING A BEAUTIFUL DISPLAY.



() KEY FEATURES

• BMAD Refrigeration System

Ensures rapid and effective cabinet cool down and maintains consistent temperature range with minimum energy consumption

• Intelligent Control System CIF

This intelligent control efficiently manages cooler temperatures based on surrounding conditions and self-adjusts to the correct temperature at any given time.

• High Efficiency Glass Door

Equipped with double panel glass and low-e film to reduce condensation. Door hinge is equipped with a self-closing system to ensure the door closes safely, and returns to original position, without any damages.

• LED Lighting System

Our LED system uses a fraction of the energy of regular fluorescent lights and requires no replacement for up seven years.

• CFC and HFC Free Cyclopentane Foam

Eco-friendly, recyclable and high efficiency cabinet insulation.

• Electronic Fan Motors

Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer lifespan fan motor.



VFS24

ESTABLISHING A **NEW STANDARD** IN THE COMMERCIAL REFRIGERATION INDUSTRY.

PRODUCT VIEWS



TOP VIEW

30 1/8"





SIDE VIEW

Warranty:

Three year limited warranty on all parts and labor, an additional two year warranty on compressor. (USA and Canada only)

Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.

Customer Service: 866-363-0079 | WWW.IMBERAFOODSERVICE.COM

() TECHNICAL SPECIFICATIONS

Exterior Dimensions	W: D: H:	30 1/8" 765 mm 30 7/8" 785 mm 78 3/4" 2000 mm
Interior Dimensions	W: D: H:	26 1/2" 672 mm 25 3/8" 646 mm 60 3/4" 1544 mm
Dimensions w/packaging	W: D: H:	32 1/4" 820 mm 29 7/8" 760 mm 82 5/8" 2100 mm
Shelf Size	W: D:	25 3/4" 653 mm 21 1/4" 541 mm
Weight Weight w/packaging		378.0 Lbs 171.0 kg 394.6 Lbs 179.0 kg
Shelves	5	

(2) REFRIGERATION DATA

Energy Consumption	10.220 kWh/day
Voltage	115/60
Horse Power	3/4
AMPS	7.0

() LOGISTIC

Trailer Loads	40': 28 53': 36
Certifications	UL:

^{*} Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (Low maintenance high performance). Dimensions rounded up to the nearest inch or millimeter. Specications subject to change without notice.