

G319 HC GRAVITY

Commercial Refrigeration 19 ft³

Energy efficient, environmentally friendly, featuring spark-free components, low refrigerant charge and the most attractive product display



Key features

Electronic Temperature Controller

Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.

Electronic Fan Motors

Enhances performance and efficiency. Uses only a fraction of the energy and offers longer life expectancy than industry standard shaded-pole motors.

Newly Designed Condenser

New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.

LED Efficiency +220 lux Minimum Output

New 5th generation constant power ultra-high efficiency LED uses lowest energy possible, with highest light output.

Spark-Free Refrigeration Components

All HC models will have spark free refrigeration components for optimal safety, per UL requirements.

G319 HC GRAVITY

Technical specifications

Exterior Dimensions		Interior Dimensions	
H: 78"	1980 mm	H: 60 3/7"	1535 mm
W: 29 1/2"	750 mm	W: 25 1/2"	648 mm
D: 26 1/6"	665 mm	D: 21 2/3"	550 mm

Usable Interior Capacity		Volume
H: 54 4/7"	1386 mm	19.20 ft ³
W: 25 2/5"	645 mm	543.7 lts
D: 21 2/3"	550 mm	

Doors	1
Door Construction	Standard Black Plastic Frame
Shelves	5
Shelf Size & Guage	W: 24 3/4" 630 mm D: 19 5/8" 497 mm

Refrigeration performance data

Refrigerant R290	2.29 oz
Energy Consumption	1.80 kWh/day*
Compressor Power	1/4 HP
Condenser	Finless, (low maintenance)
Thermostat Setting Default	Cut-Out Cut-In 32°F (0°C) - 44.6°F (7°C)


Electrical data

Power Supply	115v 60 Hz
AMPS	7 kWh/day
Cord Length	118' 3000 mm
Lighting	302.6 Lux output 9 modules 72 LED per module
Plug Type	PC-731
Controller	Imbera ETC1H controller Pre-programmed temperatures


Logistic data

Trailer Loads	53': 56 40': 30
Unit Weight w/packaging	240.52 Lbs 109.1 kg
Dimensions w/packaging	H: 81 1/2" 2070 mm W: 33 6/7" 860 mm D: 31 1/2" 800 mm


Product views




Front view



Side view



Top view



Human scale

Dimensions rounded up to the nearest inch or millimeter.
Specifications subject change without notice.



NSF/ANSI 7 COMMERCIAL REFRIGERATOR
AND/OR FREEZER
201V

Three year limited warranty is included on all parts and labor. An additional two year warranty is issued on the compressor (USA & Canada only). Operators must follow installation and operational guidelines per Imbera Users Manual. Each cooler must have its own power supply, otherwise warranty will be void.

*Energy consumption based on ANSI/ASHRAE Standard 72-2005. BMAD System (Low maintenance high performance). Dimensions rounded up to the nearest inch or millimeter. Specifications subject to change without notice.